<u>Unitization Requirements - DSCP Medical</u>

- 1. DSCP Medical's unitization requirements are based on the guidance provided via DLAI 4145.12, The DLA Packaging Program, which requires that:
- a. Cargo shall be unitized to the maximum extent practical, generally following the criteria of MIL-HDBK-774, Palletized Unit Loads, using the standard warehousing and shipping pallet, 4-way entry, 40 x 48 inch, nonreversible, winged. Pallets shall conform to ASME MH1.8, Pallet, Material Handling, Wood, Stringer Construction, 2-way and 4-way (partial), either soft-wood (preferred) or hardwood. Maximum weight of the load shall be 3,000 pounds. Maximum height shall follow the criteria of MIL-HDBK-774; however, no unitized load comprised of a number of exterior (shipping) containers shall exceed 54 inches in height, unless otherwise specified.
- b. Materiel shall be unitized to the extent practical at the time of acquisition, and will be shipped in a unitized mode whenever possible.
- 2. The unitization requirements are specified in the clear in all DSCP Medical acquisitions, both military and commercial. The unitization table also includes the following:
- a. Applicable levels of preservation and packing (i.e., packaging commercial or military, and packing commercial, Level A, or Level B) specific to the item in question.
- b. Certification Requirement for Non-Manufactured Wood Packing Materials (NMWPM), which became effective 1 October 2001.
- (1) Currently, shipments packed in/on NMWPM and destined for delivery to one of the member states of the European Union are affected by this requirement. This includes all shipments, whether sent directly to the customer, or through a Defense Depot or other consolidation point.
- (2) A listing of the current Defense consolidation points is included in the unitization table.
- 3. See the attachment for the current DSCP Medical unitization requirements.
- 1 Attachment

PREPARATION FOR DELIVERY

CERTIFICATION REQUIREMENT FOR NON-MANUFACTURED WOOD PACKING MATERIAL (NMWPM)

APPLICABLE TO ALL COMMERCIAL/GOVERNMENT EXPORT SHIPMENTS OF SUPPLIES PACKED IN/ON NMWPM AND DESTINED FOR DELIVERY TO EUROPE ON/AFTER OCTOBER 1, 2001, EITHER DIRECTLY TO THE CUSTOMER OR THROUGH A DEFENSE DEPOT OR OTHER CONSOLIDATION POINT.

-- -- -- -- -- -- --

ALL WOODEN PALLETS AND WOODEN CONTAINERS PRODUCED ENTIRELY OR IN PART OF NON-MANUFACTURED SOFTWOOD SPECIES SHALL BE CONSTRUCTED FROM HEAT-TREATED (HT TO 56 DEGREES CENTIGRADE FOR 30 MINUTES) CONIFEROUS MATERIAL AND CERTIFIED ACCORDINGLY BY AN ACCREDITED AGENCY RECOGNIZED BY THE AMERICAN LUMBER STANDARD COMMITTEE, INCORPORATED (ALSC), IN ACCORDANCE WITH THE LATEST REVISION OF THE ALSC NON-MANUFACTURED WOOD PACKING POLICY AND NON-MANUFACTURED WOOD PACKING ENFORCEMENT REGULATIONS (SEE URL: HTTP://WWW.ALSC.ORG/).

ALL WOODEN PALLETS AND WOODEN CONTAINERS PRODUCED ENTIRELY OF NON-MANUFACTURED HARDWOOD SPECIES SHALL BE IDENTIFIED BY A PERMANENT MARKING OF "NC-US", 1.25 INCHES OR GREATER IN HEIGHT, ACCOMPANIED BY THE CAGE CODE OF THE PALLET/CONTAINER MANUFACTURER AND THE MONTH AND YEAR OF THE CONTRACT. ON PALLETS, THE MARKING SHALL BE APPLIED TO THE STRINGER OR BLOCK ON DIAGONALLY OPPOSITE SIDES AND ENDS OF THE PALLET AND SHALL BE CONTRASTING AND CLEARLY VISIBLE. ON CONTAINERS, THE MARKING SHALL BE APPLIED ON A SIDE OTHER THAN THE TOP OR BOTTOM, AND SHALL BE CONTRASTING AND CLEARLY VISIBLE.

THE POINT OF ENTRY.

FAILURE TO COMPLY WITH ALL THE REQUIREMENTS OF THIS RESTRICTION MAY RESULT IN REFUSAL, DESTRUCTION, OR TREATMENT OF MATERIALS AT

-- -- -- -- -- -- --

DEFENSE CONSOLIDATION POINTS INCLUDE THE FOLLOWING:

- A. DEFENSE DISTRIBUTION DEPOTS, SUSQUEHANNA, PA, AND SAN JOAQUIN, CA
 - B. CONTAINER FREIGHT STATION, NORFOLK, VA
- C. ARMY PREPOSITIONED SHIP (APS 3)
 UPLOAD SITE, CHARLESTON, SC (DODAAC W81X89
 AND W81YUK)
- D. MARINE CORPS BLOUNT ISLAND COMMAND, JACKSONVILLE, FL 32226-3404
- E. AERIAL PORTS OF EMBARKATION,
 DOVER, DE; TRAVIS AIR FORCE BASE, CA;
 NAVAL AIR STATION, NORFOLK, VA; AND
 CHARLESTON AIR FORCE BASE, SC.

PACKAGING AND PACKING SHALL BE

(As applicable, levels of packaging (commercial/military) and packing (commercial/A/B) are stated here.)

AS SPECIFIED IN THE PROCUREMENT DOCUMENT.

UNITIZED LOADS COMMENSURATE WITH THE LEVEL OF PACKING SPECIFIED IN THE CONTRACT OR ORDER SHALL BE USED WHENEVER TOTAL QUANTITY FOR SHIPMENT TO ONE DESTINATION EXCEEDS 250 LBS (EXCLUDING THE PALLET) OR 20 CU FT. LOADS SHALL BE UNITIZED ON TYPE IV OR TYPE V 4-WAY ENTRY PALLETS.
PALLET SHALL HAVE A LENGTH OF 40 INCHES AND A WIDTH OF 48 INCHES. PALLET LOAD, INCLUDING THE PALLET, SHALL NOT EXCEED 54 INCHES IN HEIGHT, 43 INCHES IN LENGTH AND 52 INCHES IN WIDTH.

QUANTITY FOR SHIPMENT TO ONE DESTINATION OF LESS

THAN 250 LBS OR 20 CUBIC FEET NEED NOT BE PALLETIZED.

EXCEPTIONS:

A SINGLE MEDICAL ITEM HAVING A HEIGHT OF 48 INCHES OR GREATER:

IF A PROPERLY PALLETIZED LOAD (EQUIPMENT ITEM AND PALLET) EXCEEDS 54 INCHES IN HEIGHT, HEIGHT LIMITATION NEED NOT BE ADHERED TO.

A SINGLE MEDICAL ITEM HAVING DIMENSIONS EXCEEDING THE MAXIMUM PALLET LOAD LENGTH AND/OR WIDTH DIMENSIONS:

IF A SINGLE ITEM EXCEEDS THE MAXIMUM PALLET LOAD DIMENSIONS, LENGTH AND WIDTH LIMITATIONS NEED NOT BE ADHERED TO. CONTACT THE CONTRACTING OFFICER FOR ADDITIONAL GUIDANCE.

NOTE: THE PALLETIZATION STANDARD, MIL-STD-147D, HAS BEEN REDESIGNATED AS A PALLETIZATION HANDBOOK, MIL-HDBK-774 DATED 25 MARCH 1996.
THEREFORE, THIS DOCUMENT MAY NO LONGER BE CITED AS A REQUIREMENT; IT IS NOW USED FOR GUIDANCE PURPOSES ONLY. THE ONLY PHYSICAL CHANGE TO THE DOCUMENT IS THE COVER SHEET DESIGNATING IT AS A HANDBOOK. THEREFORE, IF YOU HAVE A COPY OF MIL-STD-147D ON HAND, YOU MAY USE IT FOR GUIDANCE WHEN PALLETIZING YOUR SHIPMENTS.
COPIES OF MIL-HDBK-774 MAY BE OBTAINED FROM THE DOCUMENT AUTOMATION AND PRODUCTION SERVICE (DAPS), BLDG 4D (NPM-DODSSP), 700 ROBBINS AVENUE, PHILADELPHIA, PA 19111-5094.